

配光データ一覧 Data List

スーパークール 115 150W

光色	波長データ	集光型	散光型																																				
<div style="border: 1px solid blue; padding: 10px; text-align: center;"> Marine blue マリンブルー </div>	<p>MSC-150W/BLW(N) マリンブルー</p>	<table border="1"> <caption>30° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>77760</td></tr> <tr><td>30</td><td>φ324</td><td>19440</td></tr> <tr><td>60</td><td>φ486</td><td>8640</td></tr> <tr><td>90</td><td>φ648</td><td>4860</td></tr> <tr><td>120</td><td>φ864</td><td>3110</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	77760	30	φ324	19440	60	φ486	8640	90	φ648	4860	120	φ864	3110	<table border="1"> <caption>70° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>77760</td></tr> <tr><td>30</td><td>φ420</td><td>31110</td></tr> <tr><td>60</td><td>φ840</td><td>7780</td></tr> <tr><td>90</td><td>φ1260</td><td>3460</td></tr> <tr><td>120</td><td>φ1680</td><td>1940</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	77760	30	φ420	31110	60	φ840	7780	90	φ1260	3460	120	φ1680	1940
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	77760																																					
30	φ324	19440																																					
60	φ486	8640																																					
90	φ648	4860																																					
120	φ864	3110																																					
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	77760																																					
30	φ420	31110																																					
60	φ840	7780																																					
90	φ1260	3460																																					
120	φ1680	1940																																					
<div style="border: 1px solid blue; padding: 10px; text-align: center;"> Aqua blue アクアブルー </div>	<p>MSC-150W/ABW(N) アクアブルー</p>	<table border="1"> <caption>30° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>33330</td></tr> <tr><td>30</td><td>φ324</td><td>8330</td></tr> <tr><td>60</td><td>φ486</td><td>3700</td></tr> <tr><td>90</td><td>φ648</td><td>2080</td></tr> <tr><td>120</td><td>φ864</td><td>1280</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	33330	30	φ324	8330	60	φ486	3700	90	φ648	2080	120	φ864	1280	<table border="1"> <caption>70° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>33330</td></tr> <tr><td>30</td><td>φ420</td><td>14440</td></tr> <tr><td>60</td><td>φ840</td><td>3610</td></tr> <tr><td>90</td><td>φ1260</td><td>1600</td></tr> <tr><td>120</td><td>φ1680</td><td>900</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	33330	30	φ420	14440	60	φ840	3610	90	φ1260	1600	120	φ1680	900
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	33330																																					
30	φ324	8330																																					
60	φ486	3700																																					
90	φ648	2080																																					
120	φ864	1280																																					
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	33330																																					
30	φ420	14440																																					
60	φ840	3610																																					
90	φ1260	1600																																					
120	φ1680	900																																					
<div style="border: 1px solid blue; padding: 10px; text-align: center;"> Deep blue ディープブルー </div>	<p>MSC-150W/DBW(N) ディープブルー</p>	<table border="1"> <caption>30° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>7560</td></tr> <tr><td>30</td><td>φ324</td><td>1890</td></tr> <tr><td>60</td><td>φ486</td><td>840</td></tr> <tr><td>90</td><td>φ648</td><td>470</td></tr> <tr><td>120</td><td>φ864</td><td>280</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	7560	30	φ324	1890	60	φ486	840	90	φ648	470	120	φ864	280	<table border="1"> <caption>70° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>7560</td></tr> <tr><td>30</td><td>φ420</td><td>4440</td></tr> <tr><td>60</td><td>φ840</td><td>1110</td></tr> <tr><td>90</td><td>φ1260</td><td>490</td></tr> <tr><td>120</td><td>φ1680</td><td>280</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	7560	30	φ420	4440	60	φ840	1110	90	φ1260	490	120	φ1680	280
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	7560																																					
30	φ324	1890																																					
60	φ486	840																																					
90	φ648	470																																					
120	φ864	280																																					
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	7560																																					
30	φ420	4440																																					
60	φ840	1110																																					
90	φ1260	490																																					
120	φ1680	280																																					
<div style="border: 1px solid magenta; padding: 10px; text-align: center;"> Neon Color ネオンカラー </div>	<p>MSC-150W/NCW(N) ネオンカラー</p>	<table border="1"> <caption>30° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>70000</td></tr> <tr><td>30</td><td>φ324</td><td>17500</td></tr> <tr><td>60</td><td>φ486</td><td>7780</td></tr> <tr><td>90</td><td>φ648</td><td>4380</td></tr> <tr><td>120</td><td>φ864</td><td>3110</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	70000	30	φ324	17500	60	φ486	7780	90	φ648	4380	120	φ864	3110	<table border="1"> <caption>70° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>70000</td></tr> <tr><td>30</td><td>φ420</td><td>31110</td></tr> <tr><td>60</td><td>φ840</td><td>7780</td></tr> <tr><td>90</td><td>φ1260</td><td>3460</td></tr> <tr><td>120</td><td>φ1680</td><td>1940</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	70000	30	φ420	31110	60	φ840	7780	90	φ1260	3460	120	φ1680	1940
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	70000																																					
30	φ324	17500																																					
60	φ486	7780																																					
90	φ648	4380																																					
120	φ864	3110																																					
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	70000																																					
30	φ420	31110																																					
60	φ840	7780																																					
90	φ1260	3460																																					
120	φ1680	1940																																					
<div style="border: 1px solid gray; padding: 10px; text-align: center;"> Sun White サンホワイト </div>	<p>MSC-150W/SWW(N) サンホワイト</p>	<table border="1"> <caption>30° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>91110</td></tr> <tr><td>30</td><td>φ324</td><td>22780</td></tr> <tr><td>60</td><td>φ486</td><td>10120</td></tr> <tr><td>90</td><td>φ648</td><td>5690</td></tr> <tr><td>120</td><td>φ864</td><td>4220</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	91110	30	φ324	22780	60	φ486	10120	90	φ648	5690	120	φ864	4220	<table border="1"> <caption>70° Beam Spread Data</caption> <tr><th>Distance (cm)</th><th>Beam Diameter (φ)</th><th>Illuminance (lx)</th></tr> <tr><td>0</td><td>φ152</td><td>91110</td></tr> <tr><td>30</td><td>φ420</td><td>42220</td></tr> <tr><td>60</td><td>φ840</td><td>10560</td></tr> <tr><td>90</td><td>φ1260</td><td>4680</td></tr> <tr><td>120</td><td>φ1680</td><td>2640</td></tr> </table>	Distance (cm)	Beam Diameter (φ)	Illuminance (lx)	0	φ152	91110	30	φ420	42220	60	φ840	10560	90	φ1260	4680	120	φ1680	2640
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	91110																																					
30	φ324	22780																																					
60	φ486	10120																																					
90	φ648	5690																																					
120	φ864	4220																																					
Distance (cm)	Beam Diameter (φ)	Illuminance (lx)																																					
0	φ152	91110																																					
30	φ420	42220																																					
60	φ840	10560																																					
90	φ1260	4680																																					
120	φ1680	2640																																					